3/9/1
DIALOG(R) File 351: DERWENT WPI
(c) 1997 Derwent Info Ltd. All rts. reserv.

007433676

WPI Acc No: 88-067611/198810

XRAM Acc No: C88-030474 XRPX Acc No: N88-051128

Reflection-proof optical element - has transparent plastic base with

fluorine-contg. organic polysiloxane-based thin film layer

Patent Assignee: TORAY IND INC (TORA)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Main IPC Week
JP 63021601 A 19880129 JP 86165531 A 19860716 198810 B

Priority Applications (No Type Date): JP 86165531 A 19860716 Patent Details: Patent Kind Lan Pg Filing Notes Application Patent JP 63021601 A 9

Abstract (Basic): JP 63021601 A

The reflection-proofed optical element is characterised by having, on (a) transparent plastic base with 1.52 or greater refractive index, (b) a fluorine-contg. organic polysiloxane-based thin film layer with thickness of 10-500 nm and refractive index at least by 0.02 lower than

that of the plastic base.

The fluorinated polysiloxane is pref. a polymer of fluorinated organosilicon cpd. of general formula (R1Q)SiXaY3-a (I) and/or its hydrolysate. In (I) R1 is 1-20C fluorinated alkyl gp. which may have one or more ether or ester linkage(s); Q is bivalent organic gp.; X is lower alkyl; Y is halogen, alkoxy, RCOO- where R is hydrogen or lower alkyl. The plastic base may be undercoated with a transparent coating layer contg. fine particles of inorganic oxide and having a refractive index not lower than 1.52. The optical element is produced pref. by coating the plastic base, which may have an undercoating layer, with a liq. compsn. contg. (I) and/or its hydrolysate, followed by curing at elevated temps.

USE/ADVANTAGE - The optical element combines excellent reflection-proofness with high surface hardness and improved physical strength. It permits dyeing, and is applicable to sun glass use, etc. Title Terms: REFLECT; PROOF; OPTICAL; ELEMENT; TRANSPARENT; PLASTIC; BASE; FLUORINE; CONTAIN; ORGANIC; POLYSILOXANE; BASED; THIN; FILM; LAYER

Derwent Class: A26; A89; P81

International Patent Class (Additional): C08J-007/04; G02B-001/10

File Segment: CPI; EngPI

Manual Codes (CPI/A-N): A06-A00D; A09-A02; A10-E04A; A12-B07; A12-L02A; A12-L03

Plasdoc Codes (KS): 0210 0229 0231 1306 1971 2020 2152 2198 2432 2437 2482 2493 2499 2587 2592 2594 2595 2622 2629 2654 2660 2715 2726 3310 2851 Polymer Fragment Codes (PF):

001 014 03- 04- 05- 062 064 229 231 344 346 359 38- 431 438 443 466 472 473 477 516 521 522 523 55- 551 560 561 567 57& 575 596 597 600 601 619 622 649